

QuickSet-NP Permanent Recreational Volleyball System (No Post Pads)

Uprights shall be constructed of 2"x2"x 11 ga. steel tubing designed for cementing directly into ground. Upper height adjustable post section on each upright shall slide up and down inside lower upright section allowing net height adjustments anywhere from 7' 11 5/8" (men's volleyball) down to 72" for juniors with a removable pin. Lower upright section shall be powdercoated black to protect against the elements. Upper telescoping section shall be galvanized silver.

The net shall be one meter high, be constructed of black polypropylene 3.5mm knotless woven webbing, have a Kevlar top rope and polypropylene bottom rope. The top rope shall rest in a groove of a 4" diameter steel pulley at the top of the winch standard for ease of net tensioning. The top, bottom and sides of the net shall be finished with white tarpaulin fabric with double stitched hemmed edges. The top of the net shall be tensioned by means of a high tension rope ratchet. Net bottom rope shall be tensioned by means of a ratcheting style tensioner.

Net height shall be adjustable from 7' 11 5/8" (men's volleyball) down to 72" for junior heights.

Upright standards shall carry no less than a Lifetime Limited Warranty. All other components shall carry a 2-Year Limited Warranty.

Entire QuickSet-NP system shall weigh 80 lbs.