

**First Team, Inc.**  
**Product Specifications**

**1/12/16**

**Sand Stellar Complete Recreational Volleyball System**

Uprights shall be constructed of 3 1/2" x 1/4" wall aluminum tubing. Two height adjustable clamps on each upright shall secure net allowing for quick net height adjustments anywhere from 7' 11 5/8" (men's volleyball) down to 36" (tennis) with a simple turn of the adjustment knobs. Uprights shall be powdercoated to protect against the elements.

The net shall be one meter high, be constructed of black polypropylene 3.5mm knotless woven webbing, have a Kevlar top rope and polypropylene bottom rope. The top rope shall rest in a groove of a 4" diameter steel pulley at the top of the winch standard for ease of net tensioning. The top, bottom and sides of the net shall be finished with white tarpaulin fabric with double stitched hemmed edges. The top of the net shall be tensioned by means of a high tension worm gear driven crank with non-removeable handle. Net bottom rope shall be tensioned by means of a ratcheting style tensioner.

Net height shall be infinitely variable from 7' 11 5/8" (men's volleyball) down to 36" (tennis) 42". Height setting shall be clearly identified on the upright tube.

Each standard shall be padded to a minimum height of 72" with 1 1/2" thick high-density foam covered with vinyl in customer's choice of 12 school colors. System shall include official boundary antennas.

FT5035 ground sleeves for sand shall be included. Sleeve shall protrude 34" below sand level and 2" above. Recommended only for sand courts where periodic post removal is desired.

Upright standards shall carry no less than a Lifetime Limited Warranty. All other components shall carry a 2-Year Limited Warranty. Entire system shall meet or exceed all NCAA, USVBA, NFHS and FIVB requirements for competition.

Entire Sand Stellar Complete system shall weigh 200 lbs.