

FIRST TEAM SPORTS, INC

Supermount01 Maverick – Product Specifications

1. **WALL STRUCTURE FT1998** – Construction shall be 100% fully welded. Entire wall mount structure shall be constructed of 2" square steel tubing. Wall structure shall be designed to set the backboard approximately 12" off the wall and accommodate either fan-shaped or rectangular backboards. All mounting brackets shall be no less than ¼" thick and all hardware shall be grade 5 zinc plated. Structure shall be finished with black powder coat paint. Steel structure shall secure to (3) 2"x 8" wallboards made of Dense Southern Yellow Pine. Wallboards shall be routed on four sides and be covered with a clear coat sealant. Wallboards shall be attached to support wall with fasteners provided by installer. Two turnbuckles shall extend down from top wallboard at roughly a 45 degree angle to support steel structure.
2. **BACKBOARD** - Backboard shall have perimeter dimensions of 40"x54" and be constructed of ½" thick tempered glass with an official white shooter's square and border and shall have a 5"x5" goal mounting pattern. Frame shall be aluminum extrusion held together in the corners by means of corner brackets. At the rim mounting location, glass shall be sandwiched between two cushioned steel plates. Rim mounting bolts shall pass through tubular steel bushings.
3. **RIM** - Flexible type so as to absorb the stress of player contact. The rim shall be of institutional quality with an official 5/8" diameter ring. Ring opening diameter shall be the standard 18" I.D. Rim shall have an orange powder coated finish. Heavy-duty nylon net shall be provided.
4. **WARRANTY** - Entire system shall carry a Lifetime Limited Warranty. Shipping weight shall be approximately 403#.

**FIRST TEAM SPORTS, INC.
902 COREY ROAD
HUTCHINSON, KS 67501
TOLL FREE: 888-884-6677**