

FIRST TEAM SPORTS, INC

RollaJam II Portable Basketball System - Product Specification

1. **VERTICAL UPRIGHT** - Vertical pole shall be one-piece 4" square with a minimum 11 gauge wall thickness. Posts with thinner wall thickness are not considered equal. Post shall be secured to portable base by means of two 4" square zinc plated U-bolts. Pole shall have a watertight vinyl cap to seal out moisture.

2. **BASE CONSTRUCTION** - The base is all steel construction comprised primarily of 3/16" and 11 gauge formed steel. The front of the base shall measure 30" across, base length shall be 48" front to back. The ballast area (ballast not included) shall be designed to accept (10) 4"x 8"x 16" solid cement blocks each weighing 30 lbs. (300 lbs. total). The unit shall ride on three 4" non-marking wheels for easy "one person" portability. The front wheel shall be lowered to the floor as the vertical post pivots backwards. The vertical post shall pivot backward by means of a "Post Actuator" mounted on the portable base. Pivoting post allows unit to move under any standard height doorway.

3. **EXTENSION ARMS** - Adjustable extension arms shall be constructed of dual 2" x 2" tubing. Extension shall allow for a minimum 24" from front of post to face of backboard with rim at 10' playing height. The height adjustment crank cylinder shall have a minimum 2000# capacity rating. Pole structure design shall allow for rim height to be adjusted infinitely from 10' down to 6 ½'. Two springs mounted in the extension assembly shall be included to minimize the amount of effort required to adjust the goal height when raising or lowering the unit. Pole design shall permit the rim to be mounted directly to the extension arm through the backboard so as to reduce stress on the backboard. An easy-to-read height adjustment label shall register rim height.

4. **UPRIGHT PADDING** - Unit shall be equipped with standard 2" thick foam padding. Padding shall be secured to unit via velcro attachment. Padding need not be removed during adjustment, transportation or storage.

5. **FINISH** - Powder coat black finish shall be applied to all surfaces.

6. **BACKBOARD** - Constructed of 3/8" thick acrylic with bright white screening. The framework shall be constructed from clear anodized aluminum "L" type extrusions. Overall backboard size shall be approximately 48" wide and 36" high.

7. **RIM** - Flexible type so as to absorb the stress of player contact. The rim shall be of institutional quality with an official 5/8" diameter ring. Ring opening diameter shall be the standard 18" I.D. Rim shall have an orange powder coated finish. Heavy-duty nylon net shall be provided.

8. **WARRANTY** - Complete unit carries a Lifetime Limited Warranty. Entire system weight shall be approximately 385#.

**FIRST TEAM SPORTS, INC.
902 COREY ROAD
HUTCHINSON, KS 67501
TOLL FREE: 888-884-6677**